

HSM-V-Press-503



HSM V-Press 503 vertical baling press

Easy installation and operation make the HSM V-press 503 as the ideal model for small material volumes.

HSM

Product information

To fill the press, the upper half of the doors is swung to the right. Bell-crank lever for quick and safe opening of the door. Bale removal and transport with discharge trolley. Automatic start of the pressing process after closing the door.

Technical Data

Order number:	6153111	Width x Depth x Height:	1020 x 812 x 1922 mm
EAN	4026631052313	Weight:	330 kg
Pressing power:	30 kN	Method of strapping:	vertical
Specific pressing power:	8.4 N/cm ²	Number of strappings:	2
Driving power:	1,1 kW	Type of consumables:	Strapping tape
Voltage / Frequency:	230 V / 50 Hz	Industry type:	Print & Packaging, Logistics & Distribution, Retail, Industry & Manufacturing
Cycle time when idling vacío:	27 s	Press material:	Mixed paper, Cardboard, Plastic film
Loading height:	661 mm	Use for product line:	V-Press
Volume throughput at 20kg/m³ (theor.):	0,03 t/h		
Loading aperture width x height:	700 x 470 mm		
Bale weight:	50 Kg		



HSM®



pbOffice - PBSA Group
78 Kyalami Boulevard, Kyalami Business Park,
Kyalami, Johannesburg, South Africa, 1684
T: +27 10 300 4893
www.pboffice.co.za