

HSM-V-Press-825-plus



HSM V-Press 825 plus vertical baling press

The HSM V-Press 825 is characterized by its very low transport height.

HSM

Product information

To fill the press, the upper half of the doors is folded down. Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing. HSM TCS (Torsion Control System) for monitoring press ram movement. Automatic start of the pressing process after closing the door.

Technical Data

Order number:	6152244	Width x Depth x Height:	1700 x 1046 x 2370 mm
EAN	4026631056700	Weight:	1063 kg
Pressing power:	250 kN	Method of strapping:	vertical
Specific pressing power:	26 N/cm ²	Number of strappings:	4
Driving power:	4 kW	Type of consumables:	Strapping tape
Voltage / Frequency:	400 V / 50 Hz	Industry type:	Industry & Manufacturing, Print & Packaging, Logistics & Distribution, Retail
Cycle time when idling vacio:	39 s	Press material:	Punch waste/residue, Cardboard, Mixed paper, Plastic film, Clothing
Volume throughput at 20kg/m³ (theor.):	0,14 t/h	Use for product line:	V-Press
Loading aperture width x height:	1195 x 530 mm		
Bale weight:	280 Kg		



HSM®



pbOffice - PBSA Group
78 Kyalami Boulevard, Kyalami Business Park,
Kyalami, Johannesburg, South Africa, 1684
T: +27 10 300 4893
www.pboffice.co.za